

IP-OKB

HDCVI-IP ve Analog Kontrol Keyboard



Genel Özellikler

- Kontrol Amaçlı Keyboard;Speed Dome-DVR
- IP Speed Dome-Merkezi Yönetim Platformu-IP Video server
- RS232,RS485,RS422,USB& Ağ Bağlantıları
- PTZ Fonksiyonlu Üç Eksenli Joystick
- Preset Pozisyonu,Oto.Tarama,Oto. Pan,Oto.Tur&Pattern Kontrolü
- AUX Fonksiyonları
- Menü Ekranı&Kullanıcı İşlem Prosedürü İpuçları

IP-OKB

HDCVI-IP ve Analog Kontrol Keyboard

Teknik Özellikler

Model	IP-OKB
General	
Keyboard Keypanel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RJ-45, RS232, RS485
Keyboard Communication	Direct Mode, Network Mode
	Interface: RS232/RS485 DVR Protokoller: DH1/DH2
Direct Mode	Dome Protokoller: DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-
	P1
Network Mode	Interface: RJ45 DVR/Network Dome:
	IP Address/Port/Protokoller
Display	LCD, 84mm x 31mm
Environmental	
Power Supply	Power adapter, input 100V~240V 50Hz / 60Hz,output
	DC12V/1000mA
Power Consumption	5W
Working Temperature	-10°~+55°
Working Humidity	10%~90%
Atmosphere Pressure	86kpa~106kpa
Dimension	320mmx190mmx50mm (WxDxH) (height: 100mm including joystick)
Weight	2.5KG
Connection Sample	
Direct Mod	Network Mode